

# Heated & Refrigerated Key Features

Designed for safely transporting food from a kitchen to a serving/ banqueting area



- 01. All round non-marking bumper for added protection during transfer of cabinet
- 02. Built-in handles at four sides for easy mobility
- 03. Excellent thermal efficiency, high density 75mm thick polyurethane insulation with Zero ODP (Ozone Depletion Potential) and Low GWP (Global Warming Potential)
- 04. Removable anti-tilt trayslides to prevent tipping
- 05. Self-closing doors minimise cool air loss and reduce energy consumption
- 06. Over 90° door opening allows easy loading and stock checking
- 07. 155Hmm heavy duty, non-marking swivel and braked castors for easy positioning
- 08. CoolSmart controller with clear digital display is designed for easy operation
- 09. Fitted with circulation fans to ensure even temperature and fast warm-up throughout the cabinet \*
- 10. Equipped with manual re-set safety cut-out switch to prevent overheating \*
- 11. Anti-condensation door mullion heaters #
- 12. Removable balloon type magnetic door gasket with air release points provides an excellent seal to prevent heat ingress, easy replacement and avoiding dirt traps #
- 13. Forced air refrigeration system ensures effective air circulation #
- 14. Imported, durable and energy-efficient compressor #
- 15. Evaporator with Hydrophilic coated aluminum provides high corrosion resistance properties #
- 16. Accurate helium leak detection system ensures the quality of the entire refrigeration system #
- 17. Automatic defrost ensures the evaporator working to its optimum performance #
- 18. Automatically vaporises defrost water, drainage is not required #
- 19. Designed and engineered to operate up to 43°C ambient #
- 20. Environmental-friendly CFC-free refrigerant (R134a) #
- 21. HACCP compliant

\* Available for MHC only

# Available for MRC only

# Heated & Refrigerated

## Specification

- Accommodates 2/1 GN size
- Foodsafe 304 grade stainless steel exterior (including back and base) and interior
- Fitted with cylindrical lock

## Options

1. Freezer type \*
2. 220V / 60HZ / 1PH

\* Available for MRC only



# Heated & Refrigerated Product List

MHC10SS	MHC16SS	MHC32SS
		
MRC10SS	MRC16SS	MRC32SS
		

# Heated & Refrigerated Technical Data

Model	MHC10SS	MHC16SS	MHC32SS	MRC10SS	MRC16SS	MRC32SS
Temp Range (°C)	+78 / +82	+78 / +82	+78 / +82	+1 / +4	+1 / +4	+1 / +4
<b>External Dimension (mm)</b>						
Width	807		1470		807	1470
Depth	885					
Height	1371		1768		1603	2000
<b>Internal Dimension (mm)</b>						
Width	590		1250		590	1250
Depth	650					
Height	918		1315		833	1230
<b>Thickness of 304 grade stainless steel (mm)</b>						
Exterior	0.7					
Interior	0.6					
Door	0.8					
<b>Opening Depth (mm)</b>						
1480						
<b>Capacity (cu.ft / litres)</b>						
	13.8 / 391	19.4 / 550	41.3 / 1172	13.5 / 384	19.2 / 544	40.9 / 1159
<b>Power Supply</b>						
	220V / 50HZ / 1PH					
	13 amp plug		32 amp 3p IP67 plug	13 amp plug		
<b>Power Input - Running (amps)</b>						
	6	13	18	2.4	3	3.5
<b>Rating Power (watts) *</b>						
	1320	2860	3960	528	660	770
<b>Compressor (HP)</b>						
	N/A			1/4		1/3
<b>Heat Rejection (watts) (Evaporating at -10°C in 32°C ambient)</b>						
	N/A			485		623
<b>Refrigerant</b>						
	N/A			R134a		
<b>Standard fittings</b>						
Trayslides (pair)	10	16	32	10	16	32

\* 20% increase for 60HZ power supply

V4