

# Under Broiler Key Features

Space saving, low height refrigerated counter designed for accommodating chargrills and griddles



01. Fully extendable work out drawer fitted as standard for easy accessing and better organising the food products
02. Removable cassette type condensing unit and evaporator for easy servicing with zero down time
03. Excellent thermal efficiency, high density polyurethane insulation with Zero ODP (Ozone Depletion Potential) and Low GWP (Global Warming Potential)
04. Removable balloon type magnetic door gasket with air release points provides an excellent seal to prevent heat ingress, easy replacement and avoiding dirt traps
05. 75Hmm heavy duty, non-marking swivel and braked castors for easy positioning
06. Forced air refrigeration system ensures effective air circulation
07. CoolSmart controller with clear digital display is designed for easy operation
08. Imported, durable and energy-efficient compressor
09. Evaporator with Hydrophilic coated aluminum provides high corrosion resistance properties
10. Accurate helium leak detection system ensures the quality of the entire refrigeration system
11. Automatic defrost ensures the evaporator working to its optimum performance
12. Automatically vaporises defrost water, drainage is not required
13. Designed and engineered to operate up to 43°C ambient
14. Environmental-friendly CFC-free refrigerant (R134a)
15. HACCP compliant

# Under Broiler

## Specification

- Accommodates 1/1 GN size or 2/1 GN size (UBC7(J) and UBC20(J) only)
- Foodsafe 304 grade stainless steel exterior and interior
- 1.2mm thick durable 304 grade stainless steel table top
- Galvanised steel exterior back and base

## Options

1. 304 grade stainless steel exterior back / base
2. Cylindrical lock
3. Lock plate
4. Right-hand-side condensing unit
5. Remote type condensing unit
6. Adjustable legs in lieu of castors
7. 220V / 60HZ / 1PH



## Product List

UBC2(J)	UBC4(J)	UBC6(J)
		
UBC7(J)		UBC20(J)
		

# Under Broiler Technical Data

Model	UBC2(J)	UBC4(J)	UBC6(J)	UBC7(J)	UBC20(J)
Temp Range (°C)	+1 / +4	+1 / +4	+1 / +4	+1 / +4	+1 / +4
<b>External Dimension (mm)</b>					
Width	1095	1552	2010	1300	1962
Depth	670			782	
Height	546				
<b>Internal Dimension (mm)</b>					
Width	468	925	1302	590	1253
Depth	570			682	
Height	345				
<b>Thickness of 304 grade stainless steel (mm)</b>					
Exterior	0.7				
Interior	0.6				
Drawer	0.8				
<b>Opening Depth (mm)</b>	1270			1480	
<b>Maximum loading height of drawer (mm per drawer)</b>	95				
<b>Capacity (cu.ft / litres)</b>	4.1 / 118	7.3 / 208	10.5 / 298	6.7 / 190	12.2 / 346
<b>Power Supply</b>	220V / 50HZ / 1PH				
	13 amp plug				
<b>Power Input - Running (amps)</b>	3.5				
<b>Rating Power (watts) *</b>	770				
<b>Compressor (HP)</b>	1/4		1/3		1/4
<b>Heat Rejection (watts) (Evaporating at -10°C in 32°C ambient)</b>	485		623		485
<b>Refrigerant</b>	R134a				

\* 20% increase for 60HZ power supply

V4