



Air-cooled 
 Single-phase 220V 50Hz 
 Freezer -25°C ~ -7°C 
 Refrigerator -6°C ~ +12°C

# HOSHIZAKI GN Refrigerators

New Product  
GN Series

## Main Features



- All models adapted to GN pan
- All models standardly equipped with built-in self-vaporized drip pan
- All models standardly equipped with door lock
- Internal and external materials adopt SUS304 stainless steel
- Accommodated ambient temperature up to +43°C
- Environmental-friendly refrigerant (R134a or R404a)
- Environmental-friendly polyurethane foam
- Meet HACCP compliance requirement

\*Specification is subject to change without prior notice

## Counter Drawer Refrigerators Drawer can be custom made to door upon client's request



For 1/1 GN pans

	Model	External Dimension (mm)	Internal Dimension (mm)	Capacity (L)	Temp Range (°C)	Electric Consumption (W)	Voltage
	RTC-90DDA-GN-3D	900×750×800	530×583×588	176	-6 ~ 12	225	220V 50Hz Single-phase
	RTC-90DDA-GN-2D					225	
	FTC-90DDA-GN-3D	900×750×800	530×583×588	176	-25 ~ -7	415	220V 50Hz Single-phase
	FTC-90DDA-GN-2D					395	
	RTC-125DDA-GN-6D	1250×750×800	880×583×588	294	-6 ~ 12	315	220V 50Hz Single-phase
	RTC-125DDA-GN-4D					315	
	FTC-125DDA-GN-6D	1250×750×800	880×583×588	294	-25 ~ -7	560	220V 50Hz Single-phase
	FTC-125DDA-GN-4D					560	
	RTC-167DDA-GN-9D	1670×750×800	1300×583×588	436	-6 ~ 12	315	220V 50Hz Single-phase
	RTC-167DDA-GN-6D					315	
	FTC-167DDA-GN-9D	1670×750×800	1300×583×588	436	-25 ~ -7	619	220V 50Hz Single-phase
	FTC-167DDA-GN-6D					619	

星崎香港有限公司  
HOSHIZAKI HONG KONG CO., LIMITED

Room 1201-02, 12/F, Tamson Plaza, 161 Wai Yip Street, Kwun Tong, Kln., H.K  
Tel : 852 - 2866 2108 Fax: 852 - 2866 2109  
URL : www.hoshizaki.com.hk  
Email : jacklau@hoshizaki.com.hk



Air-cooled 
 Single-phase 220V 50Hz 
 Freezer -25°C ~ -7°C
Refrigerator -6°C ~ +12°C

# HOSHIZAKI GN Refrigerators

**New Product**  
**GN Series**

**Counter Refrigerators** Glass door can be custom made upon client's request (refrigerator only)



For 1/1 GN pans

	Model	External Dimension (mm)	Internal Dimension (mm)	Capacity (L)	Temp Range	Electric Consumption (W)	Voltage
	RTC-90SDA-GN	900×750×800	530×576×588	190	-6°C~12°C	215	220V 50Hz Single-phase
	FTC-90SDA-GN				-25°C~-7°C	398	
	RTC-125SDA-GN	1250×750×800	880×576×588	301	-6°C~12°C	315	220V 50Hz Single-phase
	FTC-125SDA-GN				-25°C~-7°C	560	
	RTC-167SDA-GN	1670×750×800	1300×576×588	443	-6°C~12°C	315	220V 50Hz Single-phase
	FTC-167SDA-GN				-25°C~-7°C	560	

**Reach-in Refrigerators** Glass door can be custom made upon client's request (refrigerator only)



For 1/1 and 2/1 GN pans

	Model	External Dimension (mm)	Internal Dimension (mm)	Capacity (L)	Temp Range (°C)	Electric Consumption (W)	Voltage
	HRE-70B-CHD-GN	700×850×1990	596×676×1484	630	-6~12	302	220V 50Hz Single-phase
	HRE-70B-CLD-GN						
	HFE-70B-CHD-GN	700×850×1990	596×676×1484	630	-25~-7	481	220V 50Hz Single-phase
	HFE-70B-CLD-GN						
	HRE-140B-CHD-GN	1400×850×1990	1296×676×1484	1370	-6~12	438	220V 50Hz Single-phase
	HRE-140B-CLD-GN			1380			
	HFE-140B-CHD-GN	1400×850×1990	1296×676×1484	1360	-25~-7	658	220V 50Hz Single-phase
	HFE-140B-CLD-GN			1370			

**星崎香港有限公司**  
HOSHIZAKI HONG KONG CO., LIMITED

Room 1201-02, 12/F, Tamson Plaza, 161 Wai Yip Street, Kwun Tong, Kln., H.K  
 Tel : 852 - 2866 2108 Fax: 852 - 2866 2109  
 URL : www.hoshizaki.com.hk  
 Email : jacklau@hoshizaki.com.hk