


1. Install the ice maker properly in accordance with the instructions on location, water supply/drain connections and electrical connections stated in the instruction and installation manuals provided. Allow 10mm extra space at the installation site to meet any installation requirements (additional spacing is also required for proper air flow and pipe connections).
2. The ice production depends on the ambient and water temperatures. Refer to the instruction manual.
3. Product Code: E1FF



ITEM	Hoshizaki Cube Ice Maker	
MODEL	IM-130NE	
AC SUPPLY VOLTAGE	1 PHASE 220-240V 50Hz	
AMPERAGE	4.5A (AT.32℃, WT.21℃)	
STARTING AMPERAGE	19A	
ELECTRIC CONSUMPTION	700W (AT.32℃, WT.21℃)	
POWER FACTOR	64%	
POWER SUPPLY CAPACITY	Min. 1.25KVA (5.5A)	
ICE PRODUCTION PER 24h	Approx. 100kg(5mm)/130kg(15mm) (AT.10℃, WT.10℃)	
	Approx. 104kg(5mm)/112kg(15mm) (AT.21℃, WT.15℃)	
	Approx. 88kg(5mm)/96kg(15mm) (AT.32℃, WT.21℃)	
WATER CONSUMPTION PER 24h	Approx. 0.53m ³ (AT.10℃, WT.10℃)	
	Approx. 0.26m ³ (AT.21℃, WT.15℃)	
	Approx. 0.22m ³ (AT.32℃, WT.21℃)	
SHAPE OF ICE	Cube Approx. 28×28×32mm	
FREEZE CYCLE TIME	Approx. 22min(5φ) (AT.21℃, WT.15℃)	
ICE PRODUCTION PER CYCLE	Approx. 1.8kg/80.pcs(5φ) (AT.21℃, WT.15℃)	
MAX STORAGE CAPACITY	Approx. 50.0kg (Bin Control Setting Approx. 28kg)	
DIMENSIONS	704mm(W)×506mm(D)×1200mm(H)	
EXTERIOR	Stainless Steel, Galvanized Steel (Rear)	
INSULATION	Polyurethane Foam	
INSULATION FOAM BLOWING AGENT	Water Blown	
CONNECTIONS-ELECTRIC	Y-Type Con. (with CONT. Plug)	
CONNECTIONS-WATER SUPPLY	Inlet G3/4 (connected at rear side)	
CONNECTIONS-DRAIN	Outlet R3/4 (connected at rear side)	
ICE MAKING SYSTEM	Cell type	
HARVESTING SYSTEM	Hot Gas Defrost	
COMPRESSOR	Hermetic	
CONDENSER	Air-cooled	
HEAT REJECTION	1880W(1620kcal/h) (AT.32℃, WT.21℃)	
EVAPORATOR	Tin-plated Copper Tube on Sheet and Cells	
REFRIGERANT CONTROL	Thermostatic Expansion Valve	
REFRIGERANT CHARGE	R404A	
ICE MAKING CONTROL SYSTEM	Thermistor, Timer	Controller Board
HARVESTING CONTROL SYSTEM	Thermistor	
BIN CONTROL SYSTEM	Microswitch with Time Delay	
ICE MAKING WATER CONTROL SYSTEM	Timer, Water Pan's movement	
ELECTRICAL PROTECTION	Class I Appliance, 5A Fuse	
COMPRESSOR PROTECTION	Auto-reset Overload Protector	
ICE MAKER PROTECTION	Interlock by Controller Board	
WEIGHT	Net weight 76kg/Gross weight 84kg	
PACKAGE	Carton 830mm(W)×620mm(D)×1395mm(H)	
ACCESSORIES	Scoop, Leg, Installation Kit	
OPERATING CONDITIONS	Ambient Temp.: 1 - 40° C, Water Supply Temp.: 5-35℃ Water Supply Pressure: 0.05-0.8MPa, Voltage Range: Rated Voltage±6%	

* We reserve the right to make changes in specifications and design without prior notice.

HOSHIZAKI CUBE ICE MAKER IM-130NE

APPROVED NOTSU.M	CHECKED MIYAZAKI	DESIGNED TOMOTSUKA	DRAWN NISHIKOORI	SCALE 1/10	TRIGONOMETRY
NOTSU.M	TOMOTSUKA	DATE 2012.02.15	DATE 2011.11.23	DRAWING NO. D10255	SYMBOL △
APPROVED	DESIGNED	SYMBOL	DATE		