



HOSHIZAKI

THE HOSHIZAKI VISI COOLER - REACH IN GLASS DOOR CHILLERS

> HSRC 220



LOADING CAPACITY	HSRC 220
CANS (330ML)	216-234 nos
RGB BOTTLE (300ML)	126-132 nos
PET BOTTLE (500ML)	108-117 nos

> HSRC 350



LOADING CAPACITY	HSRC 350
CANS (330ML)	336-378 nos
RGB BOTTLE (300ML)	224-240 nos
PET BOTTLE (500ML)	168-188 nos

> HSRC 450



LOADING CAPACITY	HSRC 450
CANS (330ML)	378-490 nos
RGB BOTTLE (300ML)	275-300 nos
PET BOTTLE (500ML)	210-245 nos

> HSRC 550



LOADING CAPACITY	HSRC 550
CANS (330ML)	480-560 nos
RGB BOTTLE (300ML)	315-340 nos
PET BOTTLE (500ML)	240-280 nos


> HSRC 650



LOADING CAPACITY	HSRC 650
CANS (330ML)	560-640 nos
RGB BOTTLE (300ML)	360-385 nos
PET BOTTLE (500ML)	280-320 nos

FEATURES

- > all designs are suitable in tropical conditions - very high ambient and lower energy norms
- > safety compliant as per IEC norms
- > ingress protection class ip24
- > easy to service with its retractable refrigeration system
- > easy to replace gasket and tube light parts
- > inbuilt door handle with bottle opener with receptacle
- > self closing door



> HSRC 850



LOADING CAPACITY	HSRC 850
CANS (330ML)	780-860 nos
RGB BOTTLE (300ML)	490-525 nos
PET BOTTLE (500ML)	395-440 nos

> HSRC 1000DD



LOADING CAPACITY	HSRC 1000DD
CANS (330ML)	980-1120 nos
RGB BOTTLE (300ML)	640-720 nos
PET BOTTLE (500ML)	490-560 nos

> HSRC 1500



LOADING CAPACITY	HSRC 1500
CANS (330ML)	1440-1620 nos
RGB BOTTLE (300ML)	900-1000 nos
PET BOTTLE (500ML)	720-810 nos



HOSHIZAKI



> HSRC 1000DD



HOSHIZAKI VISI COOLER

Displaying bottled or canned drinks makes a difference when it comes properly chilled to the right temperature. The Hoshizaki range of glass door reach-in is simple yet dependable when it comes to the many tropical conditions found in Asia.

These coolers are easy to operate and all around low maintenance features are solidly backed with the HOSHIZAKI assurance of quality.

DIMENSIONS & SPECIFICATION



All HOSHIZAKI VISI COOLER - REACH IN GLASS DOOR CHILLERS

are fitted and manufactured with the Standard Technical data:

- AC supply voltage: 220-240V, 50Hz / 60Hz
- Refrigerant: R134a
- Product temperature range 0°C to 7.2°C
- Body Construction:
 - G.P Powder Coated material - both inside and outside
 - PUF (CFC Free) Insulated with thickness from 40mm to 50mm
- Adjustable Shelves

MODEL		HSRC 220	HSRC 350	HSRC 450	HSRC 550
DIMENSION (W x D x H) IN MM	EXTERNAL	W500-D655-H1447	W583-D710-H1800	W583-D710-H2050	W640-D710-H2050
	INTERNAL	W420-D506-H1042	W503-D552-H1384	W503-D552-H1634	W560-D552-H1634
	PACKED	W565-D670-H1535	W650-D720-H1885	W650-D735-H2130	W710-D735-H2130
WEIGHT IN KG	NETT	71	87	96	125
	GROSS	82	98	105	140
GROSS VOLUME IN LITRES		209	379	449	498.82
SHELVES (PCS)		3	4	5	
LIGHTNING (FLOURESCENT LAMP)	CABINET	1 nos. horizontal T5 8W	1 nos. vertical T5 21W	1 nos. vertical T5 28W	1 nos. vertical T5 28W
	CANOPY	1 nos. horizontal T5 8W			
LEGS	WHEELS	4 nos. roller wheels			
	LEVELLING LEGS	2 nos.			

• WARRANTY: 1 year parts & labour on entire unit

R1

MODEL		HSRC 650	HSRC 850	HSRC 1000DD	HSRC 1500
DIMENSION (W x D x H) IN MM	EXTERNAL	W640-D785-H2150	W765-D785-H2134	W1152-D785-H2188	W1380-D850-H2188
	INTERNAL	W560-D622-H1690	W685-D625-H1690	W1052-D612-H1675	W1280-D679-H1675
	PACKED	W685-D825-H2230	W815-D770-H2190	W1180-D765-H2270	W1451-D846-H2239
WEIGHT IN KG	NETT	116	140	190	240
	GROSS	130	152	202	255
GROSS VOLUME IN LITRES		570	711.68	1048	1422
SHELVES (PCS)		5		5+5	
LIGHTNING (FLOURESCENT LAMP)	CABINET	1 nos. vertical T5 28W	2 nos. vertical T5 28W		
	CANOPY	1 nos. horizontal T5 14W		1 nos. horizontal T5 21W	1 nos. horizontal T5 28W
LEGS	WHEELS	4 nos. roller wheels		4 nos. castor wheels (2 with locks)	6 nos. castor wheels (2 with locks)
	LEVELLING LEGS	2 nos.			

• WARRANTY: 1 year parts & labour on entire unit

R1