BOTTLE WELL TECHNICAL DATASHEET

BW600 BOTTLE WELL

BW900 BOTTLE WELL





Dimensions (mm)	External	Internal
Width	608	525
Depth	634	504 (max) 480 (min)
Height	903	555
Capacity		



BW900

Dimensions (mm)	External	Internal
Width	908	825
Depth	634	504 (max) 480 (min)
Height	903	555
Capacity		
Capacity (330ml cans/330ml bottles)		384/261

KEY FEATURES

Capacity (330ml cans/330ml bottles)

- · Hard wearing hygienic stainless steel exterior and interior
- Removable drip tray
- CoolSmart controller
- Designed and engineered to operate efficiently up to a 32°C ambient, this exceeds Climate Class 4
- Precision injected, high density 40mm polyurethane insulation.
- · Provides excellent thermal efficiency with low GWP (Global Warming Potential) and zero ODP (Ozone Depletion Potential)
- Removable lid
- Lockable lid
- Bottle opener and easy to remove catcher built in

- · Commercial forced air refrigeration system
- Easy to clean nylon coated wire dividers

240/158

OPTIONS

- · External speed rail
- · Additional bottle opener & catcher



BOTTLE WELL TECHNICAL DATA

Bottle Well	BW600	BW900
Temperature (°C)	+4/10	+4/10
Power Supply	220V/240V 50Hz/1Ph	220V/240V 50Hz/1Ph
Fuse (Amps)	13	13
Defrost	Auto off-cycle	Auto off-cycle
Fittings		
Wire dividers	1	2
Electrical Data - Standard Refrigerant		
Refrigerant	R134a	R134a
Energy Consumption (kW / 24hrs)*	2.1	2.5
Start Up (Amps)	8	8
Running (Amps)	1.75	2
Heat Rejection (kW / 24hrs)**	330	330

IMPORTANT NOTES:

*Energy consumption is tested to EN153 in 24hrs

All refrigeration equipment requires adequate ventilation for efficient and effective performance.

Williams is committed to a policy of continual product development and innovation. As such, we reserve the right to change product specifications stated without prior notice.

Williams Refrigeration Bryggen Road, North Lynn Industrial Estate King's Lynn, Norfolk. PE30 2HZ

T +44(0) 1553 817 000 Spares: +44(0) 1553 817 017 E info@williams-refrigeration.co.uk W www.williams-refrigeration.co.uk





^{**}Heat rejection is evaporating at -10°C in 32°C Ambient